



5700[®]

RIDE-ON SCRAPER

5700 Specifications

Power Supply	Battery	
Width*	24.5"	62 cm
Height	50"	127 cm
Length*	58"	147.32 cm
Weight	2,273 lb	1,031 kg
Removable Weight	185 lb front	83.9 kg front
Weight (machine only)	2,088 lb	947.1 kg
Speed	Up to 120 ft/min 160 ft/min for HS	up to 36.6 m/min 48.8 m/min for HS
Voltage	115	230
Frequency	60 Hz	50 Hz

5700DL Specifications

Length*	63"	160 cm
Weight	2,383 lb	1,080.9 kg
Removable Weight	185 lb front	83.9 kg front
Weight (machine only)	2,198 lb	997 kg

SAFETY

- A.** Automatic kill switch is triggered when the operator seat is vacant
- B.** Larger/deepened forklift pockets
- C.** E-stop knob for safety

COMFORT

- D.** Ergonomic design includes movable foot pegs, taller handles, and an adjustable seat
- E.** Hinged hood system for easy access maintenance

PERFORMANCE

- F.** Precise hydraulic steering for maneuvering in tight spaces, zero turn radius
- G.** Quick-change swivel head blade holder
- H.** Optional dual-lift, hydraulic slide plate adjusts blade pitch and angle for continuous contact with the floor
- I.** Nonmarking tires
- J.** Twelve AGM 180-amp hour batteries provide 100 percent power, speed, and torque for 90 percent of the batteries' run cycle
- K.** Compact design fits through standard door frames and elevator doors
- L.** Front caster wheels allow increased maneuverability in tight spaces
- M.** LED light for increased visibility

Special Note: the 5700 can be ordered with lifting arms, to make jobsite maneuvering easier.

5700 is available with or without the Dual Lift. The Dual Lift feature adds operator controls for adjusting blade pitch and angle while remaining seated.

INCLUDED WITH THE 5700

- Kit 5175 includes:
 - 6277-BU: 45 degree, 3" x 12" self-scoring, bevel up
 - 6284: 3" x 12" heavy-duty blade
 - 7050-12: 12" blade holder
 - 7079-2: 2" x 6" angle shank w/ carbide tip
- 5110-100: Transport Wheels
- 402929: 3/4 x 1-1/8 Wrench
- 73507-1: 7 ft extension cord
- One-year manufacturer's warranty on parts and labor

